



The Terra Spike XF™ provides deep aeration and compaction relief down to a depth of 220mm at working speeds of up to 6km/h. Productivity is the key feature of the XF derived from fewer greasing points, only six on the entire machine, its robust design and the maintenance-free belt drive system. It means less downtime and double the productivity of conventional spikers.

Terra Spike™ standard features

TwinDrive: The continuous crankshaft is driven from both sides by multi ribbed V belts delivering smooth power transmission from the tractor. The maintenance-free encapsulated drive is dust and dirt-proof. TwinDrive can be configured with various transmission ratios allowing the crankshaft speed to be adapted optimally to the available tractor power

New Crankshaft: Highly stable computer optimised crank features counter balancing weights to ensure effortless running and long service life

Quick Set Heave: Achieves a class leading 25° heave range. A simple, central and 'tool free' adjustment gives infinite heave setting between 90° and 65°

Quick Set Depth: Accurately set depths, regardless of which length of tine is fitted, just make one simple, central and 'tool free' adjustment

Vibra Stop: A key safety benefit to the operator, this is an integrated shock absorbing system which absorbs vibration

Power Pack: A central power pack helps to protect the tines from damage in extreme stony or hard conditions

Quick Fit: An integrated tine mounting and extraction system

The Terra Spike XF™ is fitted with PTO slip clutch, linkage pins, rear roller with scraper bar and a first set of 20mm diameter tines.

860 00 40	Terra Spike XF 6™	1.6m working width
861 00 40	Terra Spike XF 8™	2.1m working width

NOTE Please specify desired crank speed at time of order 345, 410 or 485 rpm.